



MAINTENANCE GUIDE

INITIAL CLEANING AFTER INSTALLATION

Immediately after installation, remove the protective film from the panel surface and clean the panels with a soft cloth and a mild cleaning solution to remove any dust, adhesive residue, or static particles that may have accumulated during installation.

1. CLEANING

- Panels can be cleaned using a soft cloth or microfiber cloth with warm water and a mild, non-abrasive cleaning agent. In most cases, a damp cloth is sufficient for regular cleaning.
- For more persistent dirt, use a diluted soap or pH-neutral detergent, then rinse with clean water and wipe dry with a soft cloth.
- Always wipe the panels dry after cleaning to avoid water spots or streaking.
- Do not use abrasive cleaners, abrasive pads, aggressive chemicals, bleach, chloride-based cleaners, or solvents, as these may damage the decorative surface.
- Avoid using steam cleaners, power washers, or high-pressure cleaning equipment.

2. PROTECTING

- Use appropriate window coverings, such as drapes, window treatments, or UV-tinted glazing, to protect the product from direct sunlight, as prolonged exposure may cause discoloration.
- Avoid impact from hard or sharp objects, which may damage the decorative surface.
- Remove spills, soap residues, or stains as soon as possible to prevent staining.
- Periodically inspect panel joints and sealants, especially in wet areas, to ensure they remain properly sealed.