



FAQ

1. IS THE SHOWER WALL SYSTEM WATERPROOF?

Yes. When installed according to the installation instructions, including the use of 100% silicone sealant in all tongue-and-groove joints, trims, corners, and perimeter edges, the Shower Wall System provides a waterproof surface suitable for shower environments. Proper substrate waterproofing in accordance with local building codes is still required.

2. CAN THE PANELS BE INSTALLED DIRECTLY OVER EXISTING TILE?

Yes. Existing ceramic tile walls can typically be covered without additional preparation, provided the surface is stable, clean, and sound. Other substrates should be properly waterproofed before installation.

3. WHAT TYPE OF ADHESIVE SHOULD BE USED?

Use an adhesive suitable for PVC wall panels, such as an MS-polymer-based adhesive. Always perform adhesion testing before installation to confirm compatibility with the substrate.

4. CAN I CUT THE PANELS TO FIT MY SHOWER?

Yes. The panels can be cut using standard woodworking tools such as a circular saw, table saw, jigsaw, or utility knife. Always measure carefully before cutting and wear appropriate personal protective equipment.

5. CAN I INSTALL THE PANELS AROUND PLUMBING FIXTURES AND SHOWER VALVES?

Yes. Openings for valves, showerheads, and other plumbing fixtures can be cut using a drill and jigsaw or hole saw. Drill from the backside of the panel to help prevent damage to the decorative surface.

6. CAN ACCESSORIES BE MOUNTED DIRECTLY TO THE PANELS?

No. Heavy accessories such as mirrors, shelves, grab bars, and hooks should not be attached directly to the panels. Fasteners should be anchored into the wall structure behind the panels and properly sealed to maintain waterproof performance.

7. WHAT WALL SURFACES ARE SUITABLE FOR INSTALLATION?

The substrate must be flat, clean, dry, plumb, and structurally sound. Suitable substrates include properly waterproofed cement board, waterproof backer boards, existing ceramic tile, and approved waterproofing systems. Raw concrete and concrete block walls are not suitable installation surfaces.

8. HOW LONG SHOULD I WAIT BEFORE USING THE SHOWER AFTER INSTALLATION?

Allow all adhesives and sealants to cure according to the manufacturer's instructions. The installation manual recommends keeping the installation dry for at least 24 hours after final sealing before use.

9. HOW DO I CLEAN AND MAINTAIN THE SHOWER WALL SYSTEM?

Clean the panels using a damp cloth and non-abrasive household cleaners. Do not use abrasive pads, aggressive chemicals, solvents, or chloride-based cleaning products, as these may damage the surface.

10. CAN THE SHOWER WALL SYSTEM BE INSTALLED IN ANY BATHROOM?

The Shower Wall System is designed for interior, temperature-controlled environments only. It should not be installed outdoors or in areas exposed to temperatures below 50°F (10°C) or above 140°F (60°C).

11. DO THE PANELS REQUIRE GROUT?

No. The Shower Wall System is a grout-free solution. Waterproof performance is achieved through proper use of silicone sealant and the tongue-and-groove joint system, eliminating the need for grout maintenance.

12. CAN THE PANELS BE INSTALLED BY A DIY HOMEOWNER?

Yes. The system is designed for straightforward installation using common tools. However, installers should carefully follow the installation instructions and all local waterproofing requirements.